

INSTALLATION INSTRUCTION FOR 4173-249/-66A

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .
AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DUDISJONCTEUR.

READ AND SAVE THESE INSTRUCTIONS

ASSEMBLING THE FIXTURE (Fig. 2)

1. Carefully remove the fixture from the carton and check that all parts are included as shown in the illustration.

2. Shut off the power at the circuit breaker and remove old fixture, including the mounting hardware.

HANGING THE FIXTURE (Fig. 1)

3. Thread all thread (E) into ceiling loop (H) until snug.
4. Thread hex nut (D) onto all thread (E). Then place lock washer (C) over the end of all thread (E).

5. Thread the other end of all thread (E) with loop (H) into mounting bar (A) until snug.

6. Take mounting bar (A) assembly and mount to ceiling junction box with the mounting screws (B) (Size:#8-32*0.6"L). The side of the mounting bar marked "GND" must face out.

7. Using proper chain pliers open one link of chain (I) and connect it to fixture loop (J).

8. By measuring, determine correct number of links needed for desired hanging height.

9. Lace the fixture wires through the chain links and slip screw collar ring (G) and canopy (F) over the chain.

10. Open one link of the other end of the chain (I) and connect it to the ceiling loop (H).

11. Feed the fixture wires through the ceiling loop (H) and all thread (E) and pull until taut.

CONNECTING THE WIRES (Fig. 3)

12. Connect the electrical wires as shown in Fig. 3, making sure that all wire connectors are secured. If your junction box has a ground wire (green or bare copper), connect the fixture's ground wire directly to the mounting bar (A) using the green screw provided. After the wires are connected, tuck them carefully inside the junction box.

COMPLETING THE INSTALLATION (Fig.2)

13. Raise canopy (F) to the ceiling. Raise the screw collar ring (G) and thread onto ceiling loop (H) protruding through canopy (F). (Fig.1)

14. Place diffuser (V) onto the fixture body (X) and secure by bending the small glass holder tabs (W).

15. Thread the pipe (P) onto the all thread (Q).

16. Place hook (M) of the rods (N) into loop (O). Then loop (L) of the rods (N) into hook (K).

17. Install (3) three medium base bulbs up to 100 watts each or CFL or LED equivalent (not included) in accordance with the fixture specification.

DO NOT EXCEED THE SPECIFIED WATTAGE!

(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

18. Secure glass diffusers (T) to metal plate (U) with screws (R) and plastic washes (S).

Your installation is now complete. Return the power to the junction box and test the fixture.

