1000-Base-SX MMF Mini GBIC Module Datasheet

MODEL: SL311LM (TL-SM311LM)

Overview

The SM311LM (TL-SM311LM) Fiber Module Cards are introduced for extending transfer distance. Attached to our managed/smart switches, they can extend the distance to 550m. Users can choose whether and which items to use the fiber modules according to the demand in order to lower cost.

Highlights

- Multi-mode MiniGBIC module

- Compatible with T3700 series, T2700 series,T2600 series, T2500 series, T1700 series, T1600 series, T1500 series, 2/3/5 series switches and MC220L

Specifications

Model	SM311LM (TL-SM311LM)
Standards and Protocols	IEEE 802.3z, CSMA/CD, TCP/IP
Wave Length	850nm
Dimensions (W*D*H)	2.2*0.5*0.5 in (55.4*13.7*12.9 mm)
Power Supply	3.3V /
Safety & Emission	FCC, CE
Cabel	Multi-mode Fiber
Fiber Type	50/125μm or 62.5/125μm Multi-mode
Max. Cable Length	550m
Data Rate	1.25Gbps
Port Type	LC/UPC
Hardware Features	• DDM • SFP-MSA • Hot Swappable
Package Contents	• SM311LM • Installation Guide
Environment	• Operating Temperature: 0℃~70℃ (32℉~158℉) • Storage Temperature: -40℃~80℃ (-40℉~176℉) • Operating Humidity: 10%~90% non-condensing • Storage Humidity: 5%~90% non-condensing

Specifications are subject to change without notice. All brands and product names are trademarks or registered trademarks of their respective holders. © 2023 TP-Link