



Philips  
CRT monitor

38 cm (15")  
XGA

105S79

## great CRT value and quality plus lead-free design

Great quality and value merge in the 105S7 CRT monitor. Easy to install, easy to personalize and compatible with both PC and Mac computers, this affordable display features lead-free design that protects your health and our environment.

### **Better front of screen experience**

- Flat Square Tube reduces distortion and reflection
- XGA 1024x768 resolution for sharper display

### **Great convenience**

- Compatibility with PC and Mac platforms
- Quick and easy to personalize On-Screen-Display control
- Easy, user friendly plug-and-play installation

# PHILIPS

# Specifications

## Picture/Display

- Display screen type: Flat Square Tube
- Panel Size: 15"/ 36 cm
- Phosphor: P22
- Recommended display area(mm): 270 x 202 mm
- Recommended Display Area(inch): 10.6" x 8.0"
- Dot pitch: 0.28 mm
- Dot Pitch (horizontal): 0.24 mm
- White Chromaticity, 5500K:  $x = 0.332$  /  $y = 0.347$
- White Chromaticity, 6500K:  $x = 0.313$  /  $y = 0.329$
- White Chromaticity, 9300K:  $x = 0.283$  /  $y = 0.297$
- Maximum Resolution: 1024 x 768 @ 60 Hz
- Optimum resolution: 800 x 600 @ 85 Hz
- Factory Preset Modes: 6 modes
- Factory Preset Mode: 640 x 480 @ 60 Hz, 640 x 480 @ 75 Hz, 720 x 400 @ 70 Hz, 800 x 600 @ 75 Hz, 800 x 600 @ 85 Hz, 1024 x 768 @ 60Hz
- Factory Preload Modes: 9 modes
- Video Dot Rate: 75 MHz
- Horizontal Scanning Frequency: 30 - 54 kHz
- Vertical Scanning Frequency: 50 - 120 Hz
- Recommended Refresh Rate: 85 Hz

## Connectivity

- Cables: D-sub Video Cable, Power Cord
- Sync input impedance: 4.7k ohm
- Video input impedance: 75 ohm
- Video input signal levels: 0.7 Vpp
- Sync Input: Separate Sync
- Video Sync Polarities: Positive and Negative
- Cable Connection: AC Power in

## Convenience

- User convenience: Menu Languages, On-screen Display
- Monitor Controls: +/- Adjust OSD, Left/Right Select Setting Item, Power On/Off
- OSD Languages: English, French, German, Spanish, Japanese, Simplified Chinese
- Plug & Play Compatibility: DDC 2B, Windows ME/2000/XP/NT
- Regulatory approvals: FCC, UL, BSMI, PSB, FDA, CCC, SABS
- Swivel: +/- 90°
- Tilt: -5° to 15°

## Accessories

- Included accessories: AC Power Cord
- User Manual

## Dimensions

- Dimensions (with base) (W x H x D): 357 x 362 x 373 mm
- Temperature range (operation): 0°C to 40°C
- Temperature range (storage): -25°C to 65°C
- Weight: 13 kg

## Power

- Consumption (On mode): 62 W (Typical)
- Consumption (Off Mode): 5 W
- Power LED indicator: Off - Amber, Operation - green
- Power supply: Built-in

# Highlights

## Flat square tube

A tube designed to reduce distortion and reflection.

## XGA, 1024 x 768 resolution

For graphics monitors, the screen resolution signifies the number of dots (pixels) on the entire screen. For example, a 1024-by-768 pixel screen is capable of displaying 1024 distinct dots on each of 768 lines, or about 786 thousand pixels. XGA provides resolutions of 640 by 480 or 1024 by 768 pixels.

## Two-platform compatibility

The ability to work with a variety of platforms; Philips monitors are compatible to connect with PC by employing a VGA connection and connect with Macintosh.

## OSD On-Screen-Display control

An on-screen panel for adjusting a monitor. The OSD is used for contrast, brightness, horizontal, vertical positioning and other monitor adjustments.

## Easy plug-and-play

Plug-and-play is a peripheral connectivity standard. A plug and play display device can be connected to a PC and operate without requiring user intervention to adjust complicated settings.



Lead Free



Issue date 2022-05-10

Version: 2.0.3

12 NC: 8639 000 15882  
EAN: 87 10895 87273 7

© 2022 Koninklijke Philips N.V.  
All Rights reserved.

Specifications are subject to change without notice.  
Trademarks are the property of Koninklijke Philips N.V.  
or their respective owners.

[www.philips.com](http://www.philips.com)