InstantFit (UL Type-A) T5

14T5HE/46-840/IF21/G/DIM 10/1

The InstantFit TLED lamps provide hassle-free installation with simple lamp-for-lamp replacements. They deliver what we promise, with at least 40% energy savings, flicker-free performance, and the life you would expect .Other lamps claim compatibility but only InstantFit (UL Type-A) has been proven to work with over 200 ballasts and drivers, delivering even light output, with proven energy savings and a long average lifetime. End users will be delighted being under these comfortable and high quality InstantFit lamps with no visible flicker and optimized optics. Energy managers will enjoy the InstantFit lamps too as they can count the savings delivered by our lamps. To enjoy more energy savings, the InstantFit lamps can be paired with the Advance TLED drivers to create a Type C system.

Product data

General Information	
Cap-Base	G5
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	200 degree(s)
Luminous Flux	2,100 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	150.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	40000-110000 Hz
Input Frequency	40000-110000 Hz
Power Consumption	14 W
Lamp Current (Max)	350 mA
Lamp Current (Min)	150 mA
Wattage Equivalent	28 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	70-105 V

InstantFit (UL Type-A) T5

UL Type	UL Type A

Temperature

Ambient temperature range	-4 °F to 113 °F
T-Case Maximum (Nom)	158 °F

Controls and Dimming

Dimmable	Yes

Mechanical and Housing

Bulb Finish	Frosted
Bulb Material	Glass
Product Length	47-1/4 inch
Bulb Shape	T5

Approval and Application

Energy Saving Product	Yes
Approval Marks	UL certificate RoHS compliance DLC compliance

Energy Consumption kWh/1000 h	- kWh
Energy Certifications	DLC Standard

Application Conditions

can it be used in closed luminaires	Yes

Product Data

Order product name	14T5HE/46-840/IF21/G/DIM 10/1
Full product name	14T5HE/46-840/IF21/G/DIM 10/1
Order code	476515
Material Nr. (12NC)	929001824104
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677476519
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677476514

Dimensional drawing



Product	D1	D2	A1	A2	A3
14T5HE/46-840/IF21/G/DIM 10/1	5/8 inch	3/4 inch	45-3/16 inch	45-1/2 inch	45-3/4 inch

Photometric data



General uniform lighting - 14T5HE/46-840/IF21/G/DIM 10/1



Light Distribution Diagram - 14T5HE/46-840/IF21/G/DIM 10/1

InstantFit (UL Type-A) T5

Photometric data



Spectral Power Distribution Colour - 14T5HE/46-840/IF21/G/DIM 10/1

Lifetime



Life Expectancy Diagram - 14T5HE/46-840/IF21/G/DIM 10/1



Life Expectancy Diagram - 14T5HE/46-840/IF21/G/DIM 10/1



Life Expectancy Diagram - 14T5HE/46-840/IF21/G/DIM 10/1



Lumen Maintenance Diagram - 14T5HE/46-840/IF21/G/DIM 10/1

InstantFit (UL Type-A) T5

Lifetime



Lumen Maintenance Diagram - 14T5HE/46-840/IF21/G/DIM 10/1

© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.